

**Date Prepared:** 01/01/2019

**SDS No.**: MP3000

Date Revised: 01/01/2019

Revision No: 1

#### 1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: MP3000

PRODUCT CODE: MP3000

**MANUFACTURER** 

24 HR. EMERGENCY TELEPHONE NUMBERS IGS INDUSTRIES INC. 1-724-222-5800 200 COUNTRY CLUB RD.

**POBOX368** 

MEADOW LANDS, PA 15347 Emergency Phone: 1-724-222-5800 **Customer Service:** 1-724-222-5800 E-Mail: SEALANT.DEPT@IGSIND.COM

#### 2. HAZARDS IDENTIFICATION

#### GHS CLASSIFICATIONS

#### Health:

Skin Irritation, Category 2

Skin Sensitization, Category 1

Skin Corrosion, Category 3

Eye Damage, Category 1

Eye Corrosion, Category 2A

Acute Toxicity (Oral), Category 4

Target Organ Toxicity (Single exposure) (Central Nervous System (CNS), kidneys), Category 2

Target Organ Toxicity (Repeated exposure) (CNS, kidneys, and liver), Category 2

## GHS LABEL

This material is skin and eye irritant. Respirable crystalline silica and RCF may be present at the end of the product lifecycle and may cause cancer (inhalation).







**CORROSIVE** 



Health hazard

SIGNAL WORD: DANGER

#### HAZARD STATEMENTS

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H302: Harmful if swallowed.



Date Prepared: 01/01/2019

SDS No. : MP3000

**Date Revised :** 01/01/2019

Revision No: 1

H402: Harmful to aquatic life.

0462B6PD: May cause lung cancer (inhalation).

# Precautionary statement(s)

## Prevention:

P101: If medical advice is needed, have product container or label at hand.

P202: Do not handle until all safety precautions have been read and understood.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362: Take off contaminated clothing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P337+P313: If eye irritation persists: Get medical advice/attention.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
PROPRIETARY POLYMER	5-20%	PROPRIETARY
PROPRIETARY POLYMER	0-5%	PROPRIETARY
Silica, Crystalline	20-60%	14808-60-7
Refractories, Fibers, Aluminosilicate	0-10%	142844-00-6
1,2-ethanediol	0-10%	107-21-1

#### 4. FIRST AID MEASURES

**EYES:** Flush with water as required. Seek medical attention.

**SKIN:** Wash with soap and water. Get medical attention if irritation develops or persists.

**INGESTION:** If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**EYES:** Redness and/or tearing. **SKIN:** Redness and/or itching.

**NOTES TO PHYSICIAN:** Treat dermatitis as a poison ivy type rash if it develops.



Date Prepared: 01/01/2019

**SDS No.**: MP3000 **Date Revised**: 01/01/2019

Revision No: 1

# 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide, Carbon Dioxide, Hydrocarbons.

## 6. ACCIDENTAL RELEASE MEASURES

**GENERAL PROCEDURES:** Sweep up debris and dispose of in accordance with local regulations. Dust can be dampened with water for containment. Personal protective equipment is recommended.

#### 7. HANDLING AND STORAGE

HANDLING: Wash hands before eating or smoking.

STORAGE: Store in a cool, dry place. Material may become excessively soft when heated or stored in an unusually warm area.

**STORAGE TEMPERATURE:** (40°F) Minimum to (120°F) Maximum

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

# **EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
	EXPOSURE LIMITS						
Chemical Name	Туре		ppm	mg/m³			
	OSHA PEL	TWA	[1]	5 mg/m3 (%SiO2 + 2) [1]			
Cilias Caratallina	ACGIH TLV	TWA	[1]	0.025 MG/M3 <sup>[1]</sup>			
Silica, Crystalline	Supplier OEL	TWA	NL	NL			
		STEL	NL	NL			
Refractories, Fibers, Aluminosilicate	Supplier OEL	TWA	0.5				
	OSHA PEL	STEL		125			
4.0 - 11-1-1	ACGIH TLV	TWA	[2]	100 [2]			
1,2-ethanediol	Supplier OEL	TWA	NL	NL			
		STEL	NL	NL			

#### Footnotes:

- 1. Respirable Dust
- 2. Aerosol

#### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Safety glasses.



**Date Prepared**: 01/01/2019

**SDS No.** : MP3000

**Date Revised:** 01/01/2019

Revision No: 1

**SKIN:** Protective gloves such as latex, nitrile, or terry cloth.

**RESPIRATORY:** Use NIOSH approved respirator if used in a closed environment where ventilation is not adequate.

**PROTECTIVE CLOTHING:** Long sleeve shirt or other covering is recommended.

WORK HYGIENIC PRACTICES: Always adhere to general workplace hygienic practices including washing before eating or

smoking.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: Pungent.

APPEARANCE: Dark brown mastic

**COLOR:** Dark Brown

**AUTOIGNITION TEMPERATURE:** (900°F)

**VAPOR PRESSURE:** ~ 0.013 kPa (72F)

**VAPOR DENSITY:**  $\sim 2.2 \text{ Air} = 1.0$ 

**BOILING POINT: None** 

SPECIFIC GRAVITY: 1.42 H2O = 1.0

#### 10. STABILITY AND REACTIVITY

**HAZARDOUS POLYMERIZATION:** None Expected.

**STABILITY:** Stable under ordinary conditions of use and storage.

#### 11. TOXICOLOGICAL INFORMATION

#### **ACUTE TOXICITY**

С	Chemical Name	ORAL LD <sub>50</sub> (rat)
1,	,2-ethanediol	4700 mg/kg (rat)

GENERAL COMMENTS: No LD50/LC50 information established relating to normal routes of occupational exposure.

#### 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** Not Established

# 13. DISPOSAL CONSIDERATIONS



**Date Prepared:** 01/01/2019

**SDS No.** : MP3000

**Date Revised:** 01/01/2019

Revision No: 1

**DISPOSAL METHOD:** Dispose of in accordance to local sanitary regulations.

#### 14. TRANSPORT INFORMATION

### **DOT (DEPARTMENT OF TRANSPORTATION)**

PROPER SHIPPING NAME: MP3000

PRIMARY HAZARD CLASS/DIVISION: Not classified as hazardous.

OTHER SHIPPING INFORMATION: Not classified as a hazardous compound. Material is able to be transported by any means

without restriction.

**NOTE:** Non-Hazardous for transportation, not a regulated substance.

## **ROAD AND RAIL (ADR/RID)**

PROPER SHIPPING NAME: MP3000

**NOTE:** Non-Hazardous for transportation, not a regulated substance.

## AIR (ICAO/IATA)

**SHIPPING NAME: MP3000** 

PRIMARY HAZARD CLASS/DIVISION: Not classified as hazardous.

**NOTE:** Non-Hazardous for transportation, not a regulated substance.

# VESSEL (IMO/IMDG)

**SHIPPING NAME: MP3000** 

PRIMARY HAZARD CLASS/DIVISION: Not classified as hazardous.

**NOTE:** Non-Hazardous for transportation, not a regulated substance.

#### CANADA TRANSPORT OF DANGEROUS GOODS

SHIPPING NAME: MP3000

PRIMARY HAZARD CLASS/DIVISION: Not classified as hazardous.

**TDG NOTE:** Non-Hazardous for transportation, not a regulated substance.

# 15. REGULATORY INFORMATION

#### **UNITED STATES**

## SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

TITLE III NOTES: Not listed for annual reporting.

## TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: All ingredients are listed on the TSCA Inventory of chemical Substances.



**Date Prepared:** 01/01/2019

**SDS No.:** MP3000 Date Revised: 01/01/2019

Revision No: 1

CALIFORNIA PROPOSITION 65: This product contains crystalline silica, some of which is respirable at the end of the product's life cycle. Crystalline silica is known to the State of California to cause cancer.

**COMMENTS** Not a regulated or hazardous material.

## 16. OTHER INFORMATION


Date Revised: 06/06/2016

REVISION SUMMARY: This SDS replaces the 09/30/2015 SDS.


**HMIS RATING** 

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	В

**NFPA CODES** 



# HAZARDOUS MATERIALS IDENTIFICATION SYSTEM



Ø∇+ **\***+ •

HMIS RATINGS NOTES:

GENERAL STATEMENTS: Respirable dust hazard is at the end of the product life cycle when the sealed joint is being disassembled. Use gloves and dust mask during clean up.



**Date Prepared:** 01/01/2019

**SDS No.**: MP3000 **Date Revised**: 01/01/2019

Revision No: 1

MANUFACTURER DISCLAIMER: IGS Industries Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precatuionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. IGS Industries Inc. makes no representations or warranties, either expressed or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly, IGS Industries Inc. assumes no responsibility for injury or damages resulting from use of or reliance upon this information.