

Date Prepared: 01/01/2019

SDS No.: STEEL SEAL

Date Revised: 01/01/2019

Revision No: 1

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: STEEL SEAL

PRODUCT CODE: STEEL SEAL

MANUFACTURER

IGS INDUSTRIES INC. 200 COUNTRY CLUB RD.

POBOX368

MEADOW LANDS, PA 15347

Emergency Phone: 1-724-222-5800 **Customer Service:** 1-724-222-5800 E-Mail: SEALANT.DEPT@IGSIND.COM

24 HR. EMERGENCY TELEPHONE NUMBERS

1-724-222-5800

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Irritation, Category 2

Skin Sensitization, Category 1

Eye Damage, Category 1

Eye Corrosion, Category 2A

Skin Corrosion, Category 3

Acute Toxicity (Oral), Category 4

Acute Toxicity (Inhalation), Category 4

GHS LABEL

This material is skin and eye irritant. Respirable crystalline silica and RCF may be present at the end of the product lifecycle and may cause cancer (inhalation).









hazard

CORROSIVE

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H402: Harmful to aquatic life.

H302 + H332: Harmful if swallowed or if inhaled.



Date Prepared: 01/01/2019

SDS No. : STEEL SEAL

Date Revised: 01/01/2019

Revision No: 1

0462B6PD: May cause lung cancer (inhalation).

H320: Causes eye irritation.

Precautionary statement(s)

Prevention:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read label before use.

P202: Do not handle until all safety precautions have been read and understood.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P270: Do not eat, drink or smoke when using this product.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P501: Dispose of contents/container to ...

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
PROPRIETARY POLYMER	40-80%	PROPRIETARY
PROPRIETARY POLYMER	0-5%	PROPRIETARY
Refractories, Fibers, Aluminosilicate	5-20%	142844-00-6
Benzyl Alcohol	5-25%	100-51-6
Aluminum (stabilized)	0-5%	7429-90-5
Mineral Oil (usp Grade)	0-5%	8042-47-5

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

INHALATION: Move to fresh air. Seek medical attention if breathing becomes irregular or becomes unconscience.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Redness and/or tearing. **SKIN:** Redness and/or itching.

NOTES TO PHYSICIAN: Treat dermatitis as a poison ivy type rash if it develops.



Date Prepared: 01/01/2019

SDS No. : STEEL SEAL

Date Revised: 01/01/2019

Revision No: 1

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: CO2 or chemical foam. Do not use water stream or halogenated compounds.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide, Carbon Dioxide, Hydrocarbons.

EXPLOSION HAZARDS: None

FIRE FIGHTING EQUIPMENT: Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Do not use water stream as flame may scatter.

FIRE EXPLOSION: None

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Ventilate area. Use chemical resistant gloves, safety glasses, and other personal protective equipment. Scoop up material and put into a tightly sealed container. Dispose of in accordance with local sanitary regulations.

LARGE SPILL: Ventilate area. Use chemical resistant gloves, safety glasses, ventilation mask, and other personal protective equipment. Soak up with absorbent material. Scoop up material and put into a container. Dispose of in accordance with local sanitary regulations.

7. HANDLING AND STORAGE

HANDLING: Follow all SDS/label precautions even after container is emptied because it may retain product residues.

STORAGE: Store in a cool, dry place. Keep container closed to prevent from drying out.

STORAGE TEMPERATURE: (40°F) Minimum to (90°F) Maximum

Notes: Sealant is a heat cured product. Cooler storage temperatures, such as refrigeration, will insure maximum shelf life.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
	EXPOSURE LIMITS				
Chemical Name	Туре		ppm	mg/m³	
Refractories, Fibers, Aluminosilicate	Supplier OEL	TWA	0.5		
Aluminum (stabilizad)	OSHA PEL TWA ACGIH TLV TWA	TWA		15T 5R	
Aluminum (stabilized)			1		

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety glasses.

SKIN: Chemically resistant gloves and sleeves should be used when applying material. Do not contact skin with material as it



Date Prepared: 01/01/2019

SDS No. : STEEL SEAL

Date Revised: 01/01/2019

Revision No: 1

may cause a poison ivy type rash in some individuals.

RESPIRATORY: Use NIOSH approved respirator if used in a closed environment where ventilation is not adequate.

PROTECTIVE CLOTHING: Long sleeve shirt or other covering is recommended.

WORK HYGIENIC PRACTICES: Always adhere to general workplace hygienic practices including washing before eating or

smoking.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: Fragrant

APPEARANCE: Fibrous Paste

COLOR: Silver gray

PERCENT VOLATILE: Not Established

FLASH POINT AND METHOD: ≥ (212°F) (TCC)

VAPOR DENSITY: > 1.04

SOLUBILITY IN WATER: Slight.

EVAPORATION RATE: Not Established **SPECIFIC GRAVITY:** 1.21 H2O = 1.0

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: None

STABILITY: Stable under ordinary conditions of use and storage.

CONDITIONS TO AVOID: Avoid exposure of uncured product to high heat or open ignition sources.

INCOMPATIBLE MATERIALS: Strong acids, caustics, oxidizers, or alkalies. Also avoid halogenated hydrocarbons.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Benzyl Alcohol	1230	2000	1000

GENERAL COMMENTS: No LD50/LC50 information established relating to normal routes of occupational exposure.

12. ECOLOGICAL INFORMATION



Date Prepared: 01/01/2019

SDS No. : STEEL SEAL

Date Revised: 01/01/2019

Revision No: 1

ENVIRONMENTAL DATA: Not Established

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance to local sanitary regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: STEEL SEAL

PRIMARY HAZARD CLASS/DIVISION: Not classified as hazardous.

OTHER SHIPPING INFORMATION: Not classified as a hazardous compound. Material is able to be transported by any means

without restriction.

NOTE: Non-Hazardous for transportation, not a regulated substance.

ROAD AND RAIL (ADR/RID)

PROPER SHIPPING NAME: STEEL SEAL

NOTE: Non-Hazardous for transportation, not a regulated substance.

AIR (ICAO/IATA)

SHIPPING NAME: STEEL SEAL

NOTE: Non-Hazardous for transportation, not a regulated substance.

VESSEL (IMO/IMDG)

SHIPPING NAME: STEEL SEAL

PRIMARY HAZARD CLASS/DIVISION: Not classified as hazardous.

NOTE: Non-Hazardous for transportation, not a regulated substance.

CANADA TRANSPORT OF DANGEROUS GOODS

SHIPPING NAME: STEEL SEAL

PRIMARY HAZARD CLASS/DIVISION: Not classified as hazardous.

TDG NOTE: Non-Hazardous for transportation, not a regulated substance.

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: None



Date Prepared: 01/01/2019

SDS No. : STEEL SEAL

Date Revised : 01/01/2019

Revision No: 1

313 REPORTABLE INGREDIENTS: None

TITLE III NOTES: Not listed for annual reporting.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: All ingredients are listed on the TSCA Inventory of chemical Substances.

CALIFORNIA PROPOSITION 65: This product contains crystalline silica, some of which is respirable at the end of the product's life cycle. Crystalline silica is known to the State of California to cause cancer.

16. OTHER INFORMATION

Date Revised: 06/06/2016

REVISION SUMMARY: This SDS replaces the 10/01/2015 SDS.

HMIS RATING HEALTH 2 FLAMMABILITY 1 PHYSICAL HAZARD 1 PERSONAL PROTECTION B



NFPA STORAGE CLASSIFICATION: Not classified as a hazardous or regulated material.



Date Prepared: 01/01/2019
SDS No.: STEEL SEAL

Date Revised: 01/01/2019

Revision No: 1

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM **HAZARD INDEX** PERSONAL PROTECTION INDEX An asterisk(*) or other DO 4 = SEVERE HAZARD designation corresponds Ø∇+ **★** 3 = SERIOUS HAZARD to additional information on a data sheet or separate C 2 = MODERATE HAZARD chronic effects notification D Additional Information 1 = SLIGHT HAZARD Ε 0 = MINIMAL HAZARD PROTECTION EQUIPMENT PERSONAL

K

Consult your supervisor or S.O.P. for "SPECIAL" handling directions

HMIS RATINGS NOTES:

GENERAL STATEMENTS: Respirable dust hazard is at the end of the product life cycle when the sealed joint is being disassembled. Use gloves and dust mask during clean up.

MANUFACTURER DISCLAIMER: IGS Industries Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precatuionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. IGS Industries Inc. makes no representations or warranties, either expressed or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly, IGS Industries Inc. assumes no responsibility for injury or damages resulting from use of or reliance upon this information.