

# SAFETY DATA SHEET

## IGS SILICONE SEALANT - CLEAR

<b>Version:</b> 1.0	<b>Revision</b> <b>Date:</b> 01/2025	<b>MSDS Number:</b> GHS – IGSRTVCLEARXTB	<b>Date Completed:</b> 01/01/2020
------------------------	---	---	--------------------------------------

### SECTION 1. IDENTIFICATION

Product Name: IGS SILICONE SEALANT - Clear

#### Manufacturer or supplier's details

Company name of supplier: IGS Industries

Address: 200 Country Club Road  
Meadowlands, PA 15347

Telephone: 800-229-1447

Emergency Telephone: 24 Hour Emergency Telephone:  
800-229-1447

#### Recommended use of the chemical and restrictions on use

Recommended use: Adhesive, binding agents

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Not a hazardous substance or mixture.

#### GHS Label Element

Not a hazardous substance or mixture.

Precautionary Statements:

#### Prevention:

P271 Use only outdoors or in a well-ventilated area.

**Other hazards:**

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture: Mixture

Chemical nature: Silicone elastomer

#### Hazardous Ingredients:

Chemical Name	CAS-No.	Concentration (%)
Silicon dioxide	7631-86-9	>= 5 - < 10
Distillates (petroleum), hydrotreated middle	64742-46-7	> = 5 - < 10

# SAFETY DATA SHEET

## IGS SILICONE SEALANT - CLEAR

<b>Version:</b> 1.0	<b>Revision</b> <b>Date:</b> 01/2025	<b>MSDS Number:</b> GHS – IGSRTVCLEARXTB	<b>Date Completed:</b> 01/01/2020
------------------------	---	---	--------------------------------------

---

### SECTION 4. FIRST AID MEASURES

If inhaled:	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact:	Wash with water and soap as a precaution. Get medical attention if symptoms occur.
In case of eye contact:	Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed:	If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed:	None known.
Protection of first-aiders:	No special precautions are necessary for first aid responders.
Notes to physician:	Treat symptomatically and supportively.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:	Water spray Alcohol-resistant foam Dry chemical Carbon dioxide (CO <sub>2</sub> )
Unsuitable extinguishing media:	None known.
Specific hazards during fire-fighting:	Exposure to combustion products may be a hazard to health.
Hazardous combustion products:	Carbon oxides Silicon oxides Formaldehyde
Specific extinguishing methods:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-	Wear self-contained breathing apparatus for firefighting if

---

# SAFETY DATA SHEET

## IGS SILICONE SEALANT - CLEAR

<b>Version:</b> 1.0	<b>Revision</b> <b>Date:</b> 01/2025	<b>MSDS Number:</b> GHS – IGSRTVCLEARXTB	<b>Date Completed:</b> 01/01/2020
------------------------	---	---	--------------------------------------

---

fighters: necessary.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures: See Engineering measures under EXPOSURE CONTROLS/ PERSONAL PROTECTION section.

Local/Total ventilation: Use only with adequate ventilation.

Advice on safe handling: Handle in accordance with good industrial hygiene and safety practice.  
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage: Keep in properly labeled containers.  
Store in accordance with the particular national regulations.

Materials to avoid: Do not store with the following product types:

---

# SAFETY DATA SHEET

## IGS SILICONE SEALANT - CLEAR

<b>Version:</b> 1.0	<b>Revision</b> <b>Date:</b> 01/2025	<b>MSDS Number:</b> GHS – IGSRTVCLEARXTB	<b>Date Completed:</b> 01/01/2020
------------------------	---	---	--------------------------------------

Strong oxidizing agents.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters/ Permissible concentration	Basis
Silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m <sup>3</sup> / %SiO <sub>2</sub> (Silica)	OSHA Z-3
		TWA	6 mg/m <sup>3</sup> (Silica)	NIOSH REL
Disyllates (petroleum), hydrotreated middle	64742-46-7	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA PO
		TWA (Mist)	5mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL

#### Engineering measures:

Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

#### Personal protective equipment

##### Respiratory protection:

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

##### Hand protection:

##### Remarks:

Wash hands before breaks and at the end of workday.

##### Eye protection:

Wear the following personal protective equipment:

# SAFETY DATA SHEET

## IGS SILICONE SEALANT - CLEAR

<b>Version:</b> 1.0	<b>Revision</b> <b>Date:</b> 01/2025	<b>MSDS Number:</b> GHS – IGSRTVCLEARXTB	<b>Date Completed:</b> 01/01/2020
------------------------	---	---	--------------------------------------

Safety goggles

Skin and body protection:

Skin should be washed after contact.

Hygiene measures:

Ensure that eye flushing systems and safety showers are located close to the working place.

When using, do not eat, drink or smoke.

Wash contaminated clothing before re-use.

These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Paste

Color:

Clear to slightly hazy, colorless

Odor:

Acetic acid

Odor Threshold:

No data available

pH:

Not applicable

Melting point/freezing point:

No data available

Initial boiling point and boiling range:

Not applicable

Flash point:

>100°C  
Method: closed cap

Evaporation rate:

Not applicable

Flammability (solid, gas):

Not classified as a flammability hazard

Upper explosion limit:

No data available

Lower explosion limit:

No data available

Vapor pressure:

Not applicable

Relative vapor density:

No data available

Relative density:

1.007

# SAFETY DATA SHEET

## IGS SILICONE SEALANT - CLEAR

<b>Version:</b> 1.0	<b>Revision</b> <b>Date:</b> 01/2025	<b>MSDS Number:</b> GHS – IGSRTVCLEARXTB	<b>Date Completed:</b> 01/01/2020
------------------------	---	---	--------------------------------------

### Solubility./(ies)

Water solubility: No data available

Partition coefficient: n-octanol/water: No data available

Autoignition temperature: No data available

Decomposition temperature: No data available

### Viscosity

Viscosity, dynamic: Not applicable

Explosive properties: Not explosive

Oxidizing properties: The substance or mixture is not classified as oxidizing.

Molecular weight: No data available

## SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Use at elevated temperatures may form highly hazardous compounds.  
Can react with strong oxidizing agents.  
Acetic acid is formed upon contact with water or humid air.  
When heated to temperatures above 150°C (300°F) in the presence of air, trace quantities of formaldehyde may be released.  
Adequate ventilation is required.  
See OSHA formaldehyde standard, 29 CFR 1910.1048.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid: None known.

Incompatible materials: Oxidizing agents.

Hazardous decomposition products:

Thermal decomposition: Formaldehyde

# SAFETY DATA SHEET

## IGS SILICONE SEALANT - CLEAR

<b>Version:</b> 1.0	<b>Revision</b> <b>Date:</b> 01/2025	<b>MSDS Number:</b> GHS – IGSRTVCLEARXTB	<b>Date Completed:</b> 01/01/2020
------------------------	---	---	--------------------------------------

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity:

Acute toxicity estimate: > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: Calculation method

#### Ingredients:

##### Silicon dioxide:

Acute oral toxicity:

LD50 (Rat): > 3,300 mg/kg

Assessment: The substance or mixture has no acute oral toxicity

Remarks: Information taken from reference works and the literature.

Acute inhalation toxicity:

LC50 (Rat):> 2.08 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhalation toxicity

Remarks: Information taken from reference works and the literature.

Acute dermal toxicity:

LD50 (Rabbit): > 5,000 mg/kg

Assessment: The substance or mixture has no acute dermal toxicity.

Remarks: Information taken from reference works and the literature.

##### **Distillates (petroleum), hydrotreated middle::**

Acute oral toxicity:

LD50 (Rat): >5,000 mg/kg

Acute inhalation toxicity:

LD50 (Rat): >5,000 mg/kg

# SAFETY DATA SHEET

## IGS SILICONE SEALANT - CLEAR

<b>Version:</b> 1.0	<b>Revision</b> <b>Date:</b> 01/2025	<b>MSDS Number:</b> GHS – IGSRTVCLEARXTB	<b>Date Completed:</b> 01/01/2020
------------------------	---	---	--------------------------------------

LC50 (Rat): 1.78 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

*Acute dermal toxicity:*

*LD50 (Rat): >2,000 mg/kg*

### **Skin corrosion/irritation**

Not classified based on available information.

### **Ingredients:**

#### **Silicon dioxide:**

Result: No skin irritation

Remarks: Information taken from reference works and the literature.

### **Serious eye damage/eye irritation:**

Not classified based on available information.

### **Ingredients:**

#### **Silicon dioxide:**

Result: No eye irritation

Remarks: Information taken from reference works and the literature.

### **Respiratory or skin sensitization**

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

### **Ingredients:**

#### **Silicon dioxide:**

Assessment: Does not cause skin sensitization.

Test Type: Skin: test type not specified

Species: Guinea pig

Remarks: No known sensitizing effect.

Information taken from reference works and the literature.

### **Germ cell mutagenicity**

Not classified based on available information.

### **Ingredients:**

#### **Silicon dioxide:**

Genotoxicity in vitro:

Result: negative



# SAFETY DATA SHEET

## IGS SILICONE SEALANT - CLEAR

<b>Version:</b> 1.0	<b>Revision</b> <b>Date:</b> 01/2025	<b>MSDS Number:</b> GHS – IGSRTVCLEARXTB	<b>Date Completed:</b> 01/01/2020
------------------------	---	---	--------------------------------------

### Acute toxicity

Not classified based on available information.

### Product:

Acute inhalation toxicity:

Acute toxicity estimate: > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: Calculation method

### Ingredients:

#### Silicon dioxide:

Acute oral toxicity:

LD50 (Rat): > 3,300 mg/kg

Assessment: The substance or mixture has no acute oral toxicity

Remarks: Information taken from reference works and the literature.

Acute inhalation toxicity:

LC50 (Rat):> 2.08 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhalation toxicity

Remarks: Information taken from reference works and the literature.

Acute dermal toxicity:

LD50 (Rabbit): > 5,000 mg/kg

Assessment: The substance or mixture has no acute dermal toxicity.

Remarks: Information taken from reference works and the literature.

### Distillates (petroleum), hydrotreated middle::

Acute oral toxicity:

LD50 (Rat): >5,000 mg/kg

Acute inhalation toxicity:

LD50 (Rat): >5,000 mg/kg

#### Exotoxicity

No data available

#### Persistence and degradability

No data available

#### Mobility in soil

No data available

#### Other adverse effects

SEC  
TION  
12.  
ECOLOGICAL  
INFORMATION

# SAFETY DATA SHEET

## IGS SILICONE SEALANT - CLEAR

<b>Version:</b> 1.0	<b>Revision</b> <b>Date:</b> 01/2025	<b>MSDS Number:</b> GHS – IGSRTVCLEARXTB	<b>Date Completed:</b> 01/01/2020
------------------------	---	---	--------------------------------------

---

No data available

---

### SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal methods**

Resource Conservation and Recovery Act (RCRA):

This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues:

Dispose of in accordance with local regulations.

Contaminated packaging:

Dispose of as unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT CONSIDERATIONS

**International Regulation****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II or MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

# SAFETY DATA SHEET

## IGS SILICONE SEALANT - CLEAR

<b>Version:</b> 1.0	<b>Revision</b> <b>Date:</b> 01/2025	<b>MSDS Number:</b> GHS – IGSRTVCLEARXTB	<b>Date Completed:</b> 01/01/2020
------------------------	---	---	--------------------------------------

### SECTION 15. REGULATORY INFORMATION

#### EPCRA – Emergency Planning and Community Right-to-Know

##### CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Acetic acid	64-19-7	5000	*
Acetic anhydride	108-24-7	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards:** No SARA Hazards.

**SARA 302:** No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313:** This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### US State Regulations

##### Pennsylvania Right To Know

Dimethyl siloxane, hydroxyl-terminated	70131-67-8	70 - 90 %
Silicon dioxide	7631-86-9	5 – 10%
Distillates (petroleum), hydrotreated middle	64742-46-7	5 – 10%
Acetic acid	64-19-7	0 – 0.1%
Acetic anhydride	108-24-7	0 – 0.1%

##### New Jersey Right To Know

Dimethyl siloxane, hydroxyl-terminated	70131-67-8	70 - 90%
Silicon dioxide	7631-86-9	5 - 10%
Distillates (petroleum), hydrotreated middle	64742-46-7	5 - 10%
Dimethyl Siloxane, Trimethylsiloxy-terminated	63148-62-9	5 – 10%

**California Prop 65** This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

#### The ingredients of this product are reported in the following inventories:

AICS: All ingredients listed or exempt.

# SAFETY DATA SHEET

## IGS SILICONE SEALANT - CLEAR

<b>Version:</b> 1.0	<b>Revision</b> <b>Date:</b> 01/2025	<b>MSDS Number:</b> GHS – IGSRTVCLEARXTB	<b>Date Completed:</b> 01/01/2020
------------------------	---	---	--------------------------------------

IECSC:	All ingredients listed or exempt
PICCS:	All ingredients listed or exempt.
DSL:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
REACH:	All ingredients (pre-)registered or exempt.
TSCA:	All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical substances.

### Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZLoC (New Zealand), PICCS (Philippines), TSCA (USA).

## SECTION 16. OTHER INFORMATION

### Further Information

NFPA:



HMIS III:

<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

### Full text of other abbreviations

NIOSH REL:	USA. NIOSH Recommended Exposure Limits.
OSHA PO:	USA. OSHA – Table Z-1 Limits for Air Contaminants – 1910.1000
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) – Table Z-1 Limits for Air Contaminants.
OSHA Z-3:	USA. Occupational Exposure Limits (OSHA) – Table Z-3 Mineral Dusts.
NIOSH REL / TWA:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek.

# SAFETY DATA SHEET

## IGS SILICONE SEALANT - CLEAR

<b>Version:</b> 1.0	<b>Revision</b> <b>Date:</b> 01/2025	<b>MSDS Number:</b> GHS – IGSRTVCLEARXTB	<b>Date Completed:</b> 01/01/2020
------------------------	---	---	--------------------------------------

NIOSH REL / ST: STEL – 15 minute TWA exposure that should not be exceeded at any time during a workday.

OSHA PO / TWA: 8-hour time weighted average.

OSHA Z-1 / TWA: 8-hour time weighted average.

OSHA Z-3 / TWA: 8-hour time weighted average.

Sources of key data used to compile the Material Safety Data Sheet: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Data: 02/16/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8